

TPS Capacitance Range		Rated Voltage DC (VR) at 85°C								(letter denotes case)
Capacitance	Code	2.5 V	4V	6.3V	10V	16V	20V	25V	35V	50V
0.15	154									A(9000)
0.22	224								A(7000)	A(7000)
0.33	334								A(6000)	A(7000)
0.47	474							A(7000)	A(6000)/B(4000)	A(6500)/B(6000)/C(2300)
0.68	684							A(6000)	A(6000)	B(4000)
1.0	105				R(9000)	A(6200)	A(3000)/R(6000)/S(6000)/T(2000)	A(4000)R(2500,4000)	A(3000)/B(2000)	B(3000)/C(2500)
1.5	155						A(3000)	A(3000)/B(1800)	A(3000)/B(2500)	C(1500,2000)
2.2	225			R(7000)	A(1800)	A(1800,3500)/T(2000)	A(3000)/B(1700)	A(2500)B(900,1200,2500)	A(1500)B(750,1500,2000)/C(1000)	C(1500)D(1200)
3.3	335			A(2100)	T(1500)	A(3500)/B(2500)	A(2500)B(1300)	A(1000,1500)B(750,1500,2000)	B(1000)/C(700)	C(1000)D(800)
4.7	475			S(4000)	A(1400)/B(1400)/R(3000,5000)	A(2000)/B(800,1500)	A(1800)/B(750,1000)	B(700,900,1500)/C(700)	B(700,1500)/C(600)D(700)	C(800)D(300,500,700)
6.8	685			A(1800)	A(1800)/B(1300)/T(1800)	A(1500)/B(600,1200)	A(1000)/B(600,1000)/C(700)	B(700)C(500,600,700)	C(350)D(150,400,500)	D(200,300,500,600)
10	106		R(3000)	A(1500)/B(1500)/R(1000,1500,3000)/T(1000)	A(900,1800)/B(1000)/P(2000) ^(M) /S(900)/T(1000,2000)	B(500,800)/C(500)/T(800,1000)/W(500,600)	B(500,1000)/C(300,500)/D(500)	B(1800)C(300,500)/D(500)	C(600)D(125,300)/E(200)/Y(250)	D(500)E(250,300,400,500)
15	156			A(700,1500)	A(1000)/B(450,600)/C(700)/T(1200)	B(500,800)/C(700)	B(500)C(400,450)	C(220,300)D(100,300)	C(350,450)D(100,300)/Y(250)	E(250)/V(250)
22	226			A(500,900)/B(375,600)/C(500)/S(900)	A(900)/B(400,500,700)/C(300)/T(800)	B(400,600)/C(150,250,300,375)/D(700)/W(500)	B(400,600)/C(100,150,400)/D(200,300)	C(275,400)D(100,200,300)	D(125,200,300,400)/E(125,200,300)/Y(200)	
33	336			A(600)/B(250,350,450,600)/T(800)	A(700)B(250,425,500,650)/C(150,375,500)/W(350)	C(100,150,225,300)D(200)W(140,175,250,400,500)/Y(300,400)	C(300)D(100,200)	D(100,200,300)E(100,175,200,300)/Y(200)	D(200,300)E(100,250,300)/V(200)	
47	476		A(500)	A(800)/B(250,350,500)/C(300)/T(1200)	B(250,350,500,650)/C(200,350)/D(100,300)/W(125,150,250)	C(110,350)D(80,100,150,200)/W(200)/X(180)/Y(250)	D(75,100,200)E(70,125,150,200,250)/X(200)Y(250)	D(125,150,250)E(80,100,125)/Y(250)	E(200,250)V(150,200)	
68	686			B(250,350,500)/C(150,200)/W(110,125,250)	B(600)C(80,100,200,300)/D(100,150)/W(100,150)/Y(100,200)	C(125,200)D(70,100,150)/F(200)/X(150)/Y(150,200,250)	D(70,150,200,300)E(125,150,200)/Y(200)	E(125,200)V(80,95,150,200)	V(150,200)	
100	107	B(200)	B(200,250,350,500)/W(100)	B(250,400)/C(75,150)/D(300)W(100,150)/Y(100)	B(400) ^(M) /C(75,100,150,200)/D(50,65,80,100,125,150)/E(125)W(150)/X(85,150,200)/Y(100,150,200)	C(200)D(60,100,125,150)E(55,100,125,150)/F(150,200) ^(M) /Y(100,150,200)	D(85,100,150)E(100,150,200)/V(60,85,100,200)	E(150) ^(M) /V(100)		
150	157	B(150)	B(250)C(70,80)	C(50,90,150,200,250)/D(50,125)/Y(40,50)	C(150)D(50,85,100)/E(100)F(200)X(100) ^(M) /Y(100,150,200)	D(60,85,100,125,150)E(100)V(45,75)/Y(200) ^(M)	V(80)	V(150) ^(M)		
220	227	B(150,200,600)/D(45)	D(40,50,100)/Y(40,50,75)	C(70,100,125,250)/D(50,100,125)/E(100)F(200)Y(100,150)	C(80,100)D(45,50,70,100)/E(50,100,125,150)/V(100)Y(100,150)	D(50,65,100,150)E(40,50,60,100)/V(40,60,100)	E(200) ^(M)			
330	337	Y(40)	C(100)D(35,45,100)/F(200)/X(100)	D(45,50,70,100)/E(50,100,125,150)/V(100)Y(100,150)	D(50,65,100,150)E(40,50,60,100)/V(40,60,100)	E(45,50,60,100,200)/V(40,60,100)				
470	477	D(35)F(200)/Y(100)	D(45,100)/E(35,45,100)	D(45,60,100,200)/E(45,50,60,100,200)/V(40,55,100)Y(150)	E(45,50,60,100,200)/V(40,60,100)					
680	687	D(35,50)E(35,50)/Y(100)	D(45,60,100)/E(40,60,100)	E(45,60,100)V(35,40,50)						
1000	108	E(30,40)Y(100) ^(M)	E(40,60)Y(25,35,40,50)	E(100) ^(M) ,V(40,50) ^(M)						
1500	158	D(100)E(50)/V(30,40) ^(M)	E(50,75)Y(60,75) ^(M)							ESR values in brackets [mΩ]

TPM Multianode Capacitance Range		Rated Voltage DC (VR) to 85°C								(letter denotes case code)
Capacitance	Code	2.5V	4V	6.3V	10V	16V	20V	25V	35V	50V
6.8	685									D(140)E(120)
10	106									E(75,100)
15	156									E(75,100)
22	226								D(70)E(60,100)	E(75,100)
33	336							D(65)	E(50,65)	
47	476						D(45,55)	D(55)E(65)	E(55,65)	
68	686					D(40,50)	E(45,55)			
100	107				Y(45) ^(M)	D(40,50)	E(35,45)			
150	157				Y(45) ^(M)	E(30,40)	E(35)			
220	227			Y(30) ^(M)	D(35)	E(25,40)				
330	337		D(25,35)	D(25,35)	D(35)E(23,35)	E(50)				
470	477		D(25,35)	D(30)E(18,23,30)	E(23,30)					
680	687		D(25)E(18,23)	E(18,23)V(23)						
1000	108	D(25)	D(25,45)E(18,23)/V(18)	E(25) ^(M) Y(20) ^(M)						
1500	158	E(12,15,18)	E(15,18)							
2200	228	E(18) ^(M)								ESR values in brackets [mΩ]

TRM Professional Multianode Capacitance Range		Rated Voltage DC (VR) to 85°C								(letter denotes case code)	
Capacitance	Code	2.5V	4V	6.3V	10V	12V	16V	20V	25V	35V	50V
10	106										E(150) [*]
15	156										
22	226										D(70)E(60,100)
33	336									D(65)	E(50,65)
47	476							D(55)	E(65)		
68	686										
100	107							D(55) [*]	E(35,45)		
150	157							D(45) [*]	E(30,40)		
220	227							D(35)E(35)			
330	337		D(35)	D(35)	E(35)						
470	477		D(35)	E(30)							
680	687		E(23)								
1000	108	D(25)	E(23)								
1500	158	E(18)	E(23)								ESR values in brackets [mΩ]

New released codes (less than 6 months old)
 *Codes under development
 Not recommended codes
 Eng. Samples - please contact manufacturer
 (M) - M tolerance only

Dimensions overview (Length x Width x Height)
 TAJ, TPS, TPM, TRJ, TRM, THJ, TAW, TLJ, TLN, TCJ, TCM, TCN
 A(3.4x1.8x1.8) B(3.7x3.0x2.1) C(6.2x3.4x2.8)
 D(7.5x4.5x3.1) E(7.5x4.5x4.3) F(6.2x3.4x2.0)
 G(3.4x1.8x1.5) H(3.7x3.0x1.5) K(3.4x1.8x1.0)
 L(3.7x3.0x1.0) M(2.25x1.5x0.9) N(2.25x1.5x1.0)
 P(2.25x1.55x1.5) R(2.25x1.5x1.2) S(3.4x1.8x1.2)
 T(3.7x3.0x1.2) U(7.5x6.3x4.3) V(7.5x4.5x2.0)
 W(6.2x3.4x1.5) X(7.5x4.5x1.5) Y(7.5x4.5x2.0)
 Z(7.5x6.3x4.5) 4(7.8x6.3x2.0) 6(15x8x2.0)

TAW Fused Capacitance Range		Rated Voltage DC (VR) at 85°C							(letter denotes case code)
Capacitance	Code	6.3V	10V	16V	20V	25V	35V	50V	
6.8	685							D(600)D(700)	
10	106							D(600)D(600)D(700)	
22	226				D(500)	D(600)			
33	336			D(600)	D(500)				
47	476		D(500)	D(800)					
100	107		D(500)					ESR values in brackets [mΩ]	

TLN Undertab-PulseCap Capacitance Range (letter denotes case code)

Capacitance		Rated Voltage DC (VR) at 85°C		
µF	Code	4V	6.3V	10V
33	336			
47	476			K(1500)/ M(6000)/ N(6000)
68	686	N(3000)*	K(5400)	K(5400)/ S(6000)
100	107	N(5200)	K(5400)/ S(5400)	K(2500)/ L(7200)*/ S(2500)
150	157	K(2500)/ S(2500)	K(2500)/ L(5400)*/ S(2500)	H(6000)/L(1300)/ S(7200)*/ T(1500)
220	227	K(2500)/ L(1300)/ S(3000)/ T(1500)	L(1000)/ S(8300)*/ T(1500)	G(7200)*/ H(6000)*/ T(1300)
330	337	G(4000)*/ L(4000)*/ S(5200)	G(5400)*/ H(3000)*	H(7200)*/ T(9600)*
470	477	G(5200)*/ H(3000)*/ T(4000)*	H(5400)*/ T(8300)*	H(9600)*
680	687	H(4000)*/ T(5200)*	H(8300)*	
1000	108	H(5200)*	Y(150)	4(100)/ 6(55)
1500	158		4(100)	6(55)
2200	228		6(55)	
3300	338	6(55)	6*	

ESR values in brackets [mΩ]

Tantalum High CV Consumer Series
TLJ Capacitance Range (letter denotes case code)

Capacitance		Rated Voltage DC to 40°C / 0.5DC to 85°C/ 0.2DC to 125°C					
µF	Code	2.5V	4V	6.3V	10V	16V	20V
10	106				N(2500)/ R(2000,3000)	S(2200)	T(1000)
15	156				R(2000)		
22	226			N(5400)/R(3500)	K(1800)/N(3800)/ R(3800)	T(1000)	
33	336		N(8000)/R(3000)	K(1700)/N(8000)/ P(3000)/R(3000)	K(1500)/N(9600)/ P(3500)/R(3500)/ S(1500)	T(1000)	
47	476		K(1500)/N(4000)/ P(3000)/R(3000)	K(1500)/N(8300)/ P(700,900,1800,2500)/ R(3200)/S(1500)	A(600)/G(1500) P(3200)/R(3200)/ S(1500)/T(600)		
68	686		K(1200)/N(8000)/ P(3000)/R(2900)/ S(1500)	A(500)/G(800)/ S(1500)/T(600)	A(1500)		
100	107		A(500)/G(800)/ N(5200)/P(2700)/ S(1400)	A(500,800)/G(800)/ P(5400)/T(800)	A(1400)/H(900)/ T(900)		
150	157		A(800)/T(800)	A(900)/G(2500)/ H(900)/T(1200)	B(500)/W(150,200)		
220	227	T(1100)	A(1100)/G(3000)/ H(900)/T(1100)	B(500)/T(2000)/W(200)	F(300)		
330	337		T(2700)/W(200)	F(300)			
680	687			Y(100,150)			
1000	108						
1500	158						

ESR values in brackets [mΩ]

TCN Undertab Polymer Capacitance Range (letter denotes case code)

Capacitance		Rated Voltage DC (VR) at 85°C		
µF	Code	4V	6.3V	10V
15	156			N(500)*
22	226			N(500)*
33	336	N(500)*	K(500)*/ N(500)*	K(500)*/ N(500)*
47	476	N(500)*	K(500)*/ N(70,200,350,500)	K(500)*/ S(500)*
68	686	K(500)*/ N(500)*	K(500)*/ S(500)*	G(150)*/ L(150)*/ S(500)*
100	107	K(500)*/ S(500)*	G(200)*/ L(200)/ S(250)*	G(150)*/ L(150)*/ S(150)*/ T(150)*
150	157	G(200)*/ L(200)*/ S(500)*	K(200)*/ L(200)/ S(200)*/ T(200)	G(150)*/ H(150)*/ T(150)*
220	227	G(200)*/ L(150)*/ S(200)*/ T(150)*	H(100,200)*/ T(200)*	H(150)*
330	337	H(150)*/ T(150)*	H(200)*	
470	477	H(150)*		

ESR values in brackets [mΩ]

New released codes (less than 6 months old)
 *Codes under development
 Not recommended codes
 Eng. Samples - please contact manufacturer
 (M) - M tolerance only

Dimensions overview (Length x Width x Height)

TAJ, TPS, TPM, TRJ, TRM, THJ, TAW, TLJ, TLL, TCJ, TCM, TCN
 A(3.4x1.8x1.8) B(3.7x3.0x2.1) C(6.2x3.4x2.8)
 D(7.5x4.5x3.1) E(7.5x4.5x4.3) F(6.2x3.4x2.0)
 G(3.4x1.8x1.5) H(3.7x3.0x1.5) K(3.4x1.8x1.0)
 L(3.7x3.0x1.0) M(2.25x1.5x0.9) N(2.25x1.5x1.0)
 P(2.25x1.55x1.5) R(2.25x1.5x1.2) S(3.4x1.8x1.2)
 T(3.7x3.0x1.2) U(7.5x6.3x4.3) V(7.5x6.3x3.75)
 W(6.2x3.4x1.5) X(7.5x4.5x1.5) Y(7.5x4.5x2.0)
 Z(7.5x6.3x4.65) 4(7.8x6.3x2.0) 6(15x8x2.0)

TAC, TLC, TPC

A(3.4x1.8x1.8) B(3.7x3.0x1.5) C(3.4x1.8x1.00)
 H(2.2x1.5x1.0) J(1.8x1.0x0.75) K(1.2x0.7x0.7)
 L(1.8x1.0x1.0) M(2.2x1.0x1.0) N(1.05x0.5x0.5)
 Q(2.2x1.5x1.2) R(2.2x1.5x1.5) S(3.4x1.8x1.2)
 T(3.7x3.0x1.2) U(2.2x1.5x0.6) V(3.4x1.8x0.75)
 Z(1.8x0.7x0.7)

TCM Polymer Multianode Capacitance Range (letter denotes case code)

Capacitance		Rated Voltage DC (VR) at 85°C						
µF	Code	4V	6.3V	10V	16V	20V	25V	35V
22	226							E(25)
33	336							
47	476							
68	686							
100	107							
150	157							
220	227							
330	337				E(10,15)			
470	477							
680	687							
1000	108	E(10,12)						
1500	158							
2200	228							

ESR values in brackets [mΩ]

TCJ Polymer Capacitance Range

(letter denotes case)

Capacitance		105°C only D,Y Case Size	105°C only D,Y Case Size	105°C only R 47/6.3, N,D,Y, K47/6.3(150,200), B150/6.3(35),T47/6.3(70)68,100/6.3	105°C only D,Y Case Size	105°C only D,E,Y Case Size	105°C	105°C	105°C	105°C	105°C	105°C	105°C	
µF	Code	2.5V	4V	6.3V	10V	16V	20V	25V	35V	50V	63V	75V	100V	125V
0.47	474													
0.68	684									B(400)		B(400)		
1.0	105							N*/P(500)	A(250)*	A*/B(300)		B(300)/ C(300)		
1.5	155								B(200)	B(300)/C(300)		C(300)		
2.2	225								B(200)	C(300)		C(200)		
3.3	335								B(200)	C(200)		C(200)		D(250)
4.7	475													
6.8	685													
10	106			A(300)/N(200*,500)/ R(500)	A(300)	A(200)/B(200)/ T(150,200)		B(150)	B(200)/ C(200)/Y(70)	D(120)/ E(70,100)		B(400)		
15	156		A(300)	A(300)	A(200)	B(150)		B(100,150)/ Y(70,200)*	D(70,100)/ W*/ Y(200)*	E(70,100)		B(300)/ C(300)		
22	226		A(300)	A(300)/K(400)/N(500)/ R(500)/S(400)/T(150)	B(300)/T(150)	B(150)	Y(70)	B(150)/C(100)/ D(60,100)/Y(70)	D(70,100)/ Y(70)*			C(300)		
33	336		A(300)	A(200)/B(70,200)/T(150)	B(70,200)/C(100)/ T(70,150)	Y(55,70)	Y(70)	D(60,100)/ E(50)	D(70,100)/ E(55,70)			C(200)		
47	476		A(200)/T(80)	A(200)/B(70)/K(150/200/400)/ P(500)/R(500)/T(70,80,120)	B(70)/C(100)	Y(55,70)	D(55)/ Y(70)	D(60,100)/ E(50)	E(55)			D(200)/ D(120)		
68	686	A(250)	A(250)/B(70)/ T(80)	B(55,70)/C(100)/T(200)/W(70)				D(45,55)/ Y(45,55)	D(55)/ E(45)			D(120)/ E(100,150)		
100	107	A(200)/ B(70)	A(200)/B(70)/ G(300)/ T(150)	A(70)*/B(45,69,70)/ T(200)		D(45,55)/ Y(45,55)	E(40)	D(55)/ E(45)	E(80)			D(120) V(250)		
150	157	B(70)	B(70)	B(35,45,69,70)/H(200)/ W(40,70)		D(45,55)/ Y(45,55)	E(40)							
220	227	A(35)*	B(45,70)	B(70,200)/D(50)/W(100)*/Y(50)		D(40,50)/ Y(40,50)								
330	337		D(50)/Y(50)	D(40,50)/Y(40,50)										
470	477	D(50)/Y(50)	D(50)/Y(50)											

ESR values in brackets [mΩ]

F- Series



F38 Undertab, Frameless Capacitance Range (letter denotes case code)			
Capacitance		Rated voltage DC (Vr) to 85°C	
µF	Code	4V (0G)	6.3V (J)
2.2	225		M
4.7	475		M
10	106		M
22	226		M, S
47	476		M, S
100	107	S	

F91 Low ESR Capacitance Range (letter denotes case code)			
Capacitance		Rated voltage DC (Vr) to 85°C	
µF	Code	4V (0G)	10V (1A)
68	686		C
100	107		C
150	157	C	C
220	227	C	C,N
330	337	N	N
470	477	N	N
680	687	N	N

F72 Conformal Capacitance Range (letter denotes case code)					
Capacitance		Rated voltage DC (Vr) to 85°C			
µF	Code	4V (0G)	6V (0J)	10V (1A)	16V (1C)
33	336				R
47	476			R	R
68	686		R	R	R
100	107	R	R	R	
150	157	R	R	R	
220	227	R	R	R	
330	337	R	R	R	
470	477				M
680	687				M
1000	108		M	M	
1500	158		M		

F75 Conformal Capacitance Range (letter denotes case code)					
Capacitance		Rated voltage DC (Vr) to 85°C			
µF	Code	4V (0G)	6V (0J)	10V (1A)	16V (1C)
68	686				C
100	107				C
150	157			C	D
220	227		C	C,D	R
330	337	C	C,D		
470	477	C,D	U,D	U,R	
680	687	D	U,D,R		
1000	108	D,R	U,R		
1500	158	R			
2200	228	R			

New released codes (less than 6 months old)
 *Codes under development
 Not recommended codes
 Eng. Samples - please contact manufacturer
 (M) - M tolerance only

F92 Low profile Capacitance Range (letter denotes case code)								
Capacitance		Rated voltage DC (Vr) to 85°C						
µF	Code	4V (0G)	6.3V (0J)	10V (1A)	16V (1C)	20V (1D)	25V (1E)	35V (1V)
0.22	224							A
0.33	334							A
0.47	474				P	P,A		A
0.68	684				P	A		A
1.0	105			P	P	P,A	P,A	A
1.5	155			P	P	A		A
2.2	225		P	P	P,A	P,A	A,B	B
3.3	335	P	P	P,A	A			B
4.7	475	P	P	P,A	P,A,B	A,B	A,B	
6.8	685	P	P	P,A	B			
10	106	P,A	P,A	P,A	A,B	B		
15	156	P	P,A	A				
22	226	P,A	P,A	A,B	B			
33	336	P,A	A,B	B				
47	476	P,A,B	A,B	B				
68	686	A,B						
100	107	A,B	A,B					
150	157	B						
220	227	B						

F93 Capacitance Range (letter denotes case code)									
Capacitance		Rated voltage DC (Vr) to 85°C							
µF	Code	4V (0G)	6.3V (0J)	10V (1A)	16V (1C)	20V (1D)	25V (1E)	35V (1V)	
0.68	684								A
1.0	105					A		A	A
1.5	155							A	A
2.2	225				A		A	A	A,B
3.3	335				A		A	A	B
4.7	475				A		A,B	A,B	B,C
6.8	685			A	A	A,B	A,B	C	C
10	106		A	A	A	A,B	A,B	B,C	C
15	156		A	A	A,B	C		C	N
22	226	A	A	A,B	A,B,C	B,C	C,N	C,N	N
33	336	A	A	A,B	B,C	B,C	C,N	N	N
47	476	A	A,B	A,B,C	B,C,N	C,N	N	N	
68	686	A	A,B	B,C	N			N	
100	107	A,B	A,B,C	B,C,N	C,N				
150	157	B	B,C	C,N	N				
220	227	A,B,C	B,C,N	N	N				
330	337	C	N	N					
470	477	N	N						
680	687	N							

F95 Conformal Capacitance Range (letter denotes case code)								
Capacitance		Rated voltage DC (Vr) to 85°C						
µF	Code	4V (0G)	6.3V (0J)	10V (1A)	16V (1C)	20V (1D)	25V (1E)	35V (1V)
1.0	105							R, P, S
1.5	155							
2.2	225					P		R, P, A
3.3	335							
4.7	475					R, P	S, A	P, Q, S, A, B
6.8	685							Q, S
10	106			R, P	P, Q, S, A	S, A, B	A, T, B	
15	156			P	S, A			
22	226		R	P, Q, S, A	Q, S, A, T, B	B		
33	336		R, P	P, Q, S, A	A, T, B			
47	476	R	P	P, Q, S, A, T, B	B			
68	686			P	B			
100	107	P, S, A	P, Q, S, A, T, B	S, A, T, B				
150	157	P, B	B					
220	227	P, Q, S, A, T, B	S, A, T, B					
330	337	P, S, A, T, B	B					
470	477	P, A, T, B	B					
680	687	T						

F97 Performance Capacitance Range (letter denotes case code)								
Capacitance		Rated voltage DC (Vr) to 85°C						
µF	Code	6.3V (0J)	10V (1A)	16V (1C)	20V (1D)	25V (1E)	35V (1V)	
0.47	474					A	A	A
0.68	684					A	A	A
1.0	105					A	A	A
1.5	155					A	A	A,B
2.2	225				A	A	A	B
3.3	335		A	A	A	B		B,C
4.7	475		A	A,B	A,B	A,B	B	C
6.8	685		A,B	B	B	B,C	C	C,N
10	106		A,B	A,B,C	A,B,C	B,C	C,N	N
15	156		B	B	B,C	N	C,N	
22	226		A,B	A,B	B,C,N	C,N	N	
33	336		A,C	B,C,N	B,C,N		N	
47	476		B,C	B,C,N	C,N			N
68	686		N	N				
100	107		N	C,N				

Dimensions overview (Length x Width x Height)
 F38, F91, F93, F97, F98
 A(3.4x1.8x1.8) B(3.7x3.0x2.1) C(6.2x3.4x2.7)
 M(1.8x1.05x0.9) N(7.5x4.5x3.0) S(2.2x1.45x0.9)
 U(1.15x0.65x0.6)

F92
 A(3.4x1.8x1.2) B(3.6x3.0x1.2) P(2.2x1.35x1.2)

F95, AUDIO F95
 A(3.5x2.0x1.6) B(3.7x3.0x2.0) P(2.5x1.55x1.2)
 Q(3.4x1.8x1.0) R(2.5x1.55x0.65) S(3.5x1.9x1.2)
 T(3.7x2.9x1.2)

F72
 M(7.5x6.3x2.0) R(7.5x6.3x1.5)

F75
 C(7.4x3.5x2.8) D(7.6x4.6x3.1) R(7.5x6.3x3.8)
 U(7.4x3.5x2.0)

AUDIO F95 Conformal Capacitance Range (letter denotes case code)				
Capacitance		Rated voltage DC (Vr) to 85°C		
µF	Code	4V (0G)	6V (0J)	10V (1A)
68	686	S	S	B
100	107	S	S, T	B
150	157	S	A	
220	227	P, S, T	A, T, B	
330	337	T	B	
470	477	T, B	B	
680	687	T, B		

F98 HiCV Capacitance Range (letter denotes case code)							
Capacitance		Rated voltage DC (Vr) to 85°C					
µF	Code	4V (0G)	6.3V (0J)	10V (1A)	16V (1C)	20V (1D)	25V (1E)
1.0	105				M	M	M
2.2	225			U, M	M		
4.7	475	U	U, M	U, M	M		
10	106	U	U, M	M	S		
22	226	M	M	M, S			
33	336	M	M	M, S			
47	476	M	M, S	S			
68	686	M, S					
100	107	M, S	S				
220	227	S					

Issued by: Technical Marketing Team
 Tantalum Division
 AVX Czech Republic

TECHNICAL ASSISTANCE: techsales-tantalum@eur.avx.com
 MORE DETAILS AT www.avx.com